

PRICE LIST NO. 157

W.E.F. 15-03-2022



ELC

INDUSTRIAL VALVES



VALVES-COCKS & BOILER MOUNTINGS

Quality Policy

We are committed to manufacture & supply the quality valves to our customers to their entire satisfaction and will strive hard to improve the effectiveness of the established quality management system.

Manohar Dhawan
(Mg. Partner)

Guarantee

Free replacement of any piece of our ELEMS products for manufacturing defect is guaranteed provided the same is returned to us without misuse or careless handling

	NAME OF ARTICLE	MM	INCH	PRICE RS.
E-01	 G.M. ELEMS WHEEL VALVE POPULAR Screwed Female Ends Light Pattern Hyd. Tested 10 Kg/cm² (150 lbs.)	15	1/2	312.00
		20	3/4	510.00
		25	1	649.00
		32	1-1/4	1102.00
		40	1-1/2	1403.00
		50	2	2122.00
		65	2-1/2	4047.00
		80	3	5966.00
		100	4	11126.00
E-02	 G.M. ELEMS WHEEL VALVE No.4 Screwed Female Ends Medium Pattern Hyd. Tested 20 Kg/cm² (300 lbs.)	4,8,10	1/8, 1/4, 3/8	396.00
		15	1/2	460.00
		20	3/4	710.00
		25	1	1041.00
		32	1-1/4	1589.00
		40	1-1/2	1985.00
		50	2	3389.00
		65	2-1/2	5532.00
		80	3	8578.00
		100	4	15249.00
		125	5	30577.00
		150	6	46371.00
E-03	 G.M. ELEMS WHEEL VALVE No.5 Screwed Female Ends Heavy Pattern Hyd. Tested 35 Kg/cm² (500 lbs.)	8,10	1/4, 3/8	625.00
		15	1/2	697.00
		20	3/4	1186.00
		25	1	1756.00
		32	1-1/4	2482.00
		40	1-1/2	3497.00
		50	2	5396.00
		65	2-1/2	9142.00
		80	3	13241.00
		100	4	21025.00
E-04	 G.M. ELEMS WHEEL VALVE No. 8 Flanged Ends B.S. Table "D" Flanges Medium Pattern Hyd. Tested 20 Kg/cm² (300 lbs.)	15	1/2	2156.00
		20	3/4	2711.00
		25	1	3721.00
		32	1-1/4	5156.00
		40	1-1/2	6301.00
		50	2	8646.00
		65	2-1/2	11302.00
		80	3	17376.00
		100	4	31263.00
		125	5	55595.00
		150	6	72358.00
E-05	 G.M. ELEMS UNION BONNET WHEEL VALVE No.9 Screwed Female Ends Heavy Pattern Hyd. Tested 40 Kg/cm² (600 lbs.)	8,10	1/4, 3/8	1580.00
		15	1/2	1633.00
		20	3/4	2453.00
		25	1	3489.00
		32	1-1/4	5124.00
		40	1-1/2	7015.00
		50	2	10825.00
		65	2-1/2	18764.00
		80	3	28019.00
		100	4	44889.00

	NAME OF ARTICLE	MM	INCH	PRICE RS.
 E-06	G.M. ELEMS	15	1/2	3864.00
	UNION BONNET WHEEL	20	3/4	4347.00
	VALVE No.9F	25	1	6064.00
	Flanged Ends	32	1-1/4	9291.00
	B.S. Table "F" Flanges	40	1-1/2	11205.00
	with Renewable Stainless Steel Trim	50	2	17318.00
	Hyd. Tested 40 Kg/cm ²	65	2-1/2	33260.00
	(600 lbs.)	80	3	36975.00
		100	4	54270.00
 E-07	G.M. ELEMS	15	1/2	2490.00
	WHEEL VALVE No.5F	20	3/4	3215.00
	Flanged Ends	25	1	4456.00
	B.S. Table "F" Flanges	32	1-1/4	7120.00
	Heavy Pattern	40	1-1/2	8948.00
	Hyd. Tested 35 Kg/cm ²	50	2	12045.00
	(500 lbs.)	65	2-1/2	19238.00
		80	3	25343.00
		100	4	34062.00
 E-08	G.M. ELEMS	8,10	1/4, 3/8	440.00
	ANGLE WHEEL	15	1/2	544.00
	VALVE No. 4	20	3/4	814.00
	Screwed Female Ends	25	1	1096.00
	Medium Pattern	32	1-1/4	1866.00
	Hyd. Tested 20 Kg/cm ²	40	1-1/2	2325.00
	(300 lbs.)	50	2	3981.00
 E-09	G.M. ELEMS	15	1/2	486.00
	GATE VALVE POPULAR	20	3/4	612.00
	Screwed Female Ends	25	1	868.00
	Light Pattern	32	1-1/4	1319.00
	Hyd. Tested 20 Kg/cm ²	40	1-1/2	1756.00
	(300 lbs.)	50	2	2332.00
		65	2-1/2	4846.00
		80	3	6321.00
		100	4	13662.00
 E-10	G.M. ELEMS	50	2	3190.00
	FULLWAY VALVE No. 571			
	Screwed Female Ends			
	Medium Pattern			
	Hyd. Tested 20 Kg/cm ²			
	(300 lbs.)			


	NAME OF ARTICLE	MM	INCH	PRICE RS.
E-11	 G.M. ELEMS FULLWAY VALVE PEGLER Screwed Female Ends Pegler Type Hyd. Tested 20 Kg/cm² (300 lbs.)	8, 10	1/4, 3/8	658.00
		15	1/2	714.00
		20	3/4	956.00
		25	1	1426.00
		32	1-1/4	1941.00
		40	1-1/2	2499.00
		50	2	3948.00
		65	2-1/2	6399.00
E-12	 G.M. ELEMS FULLWAY VALVE No. 571C Screwed Female Ends Standard Pattern Hyd. Tested 35 Kg/cm² (500 lbs.)	80	3	9198.00
		100	4	19689.00
		15	1/2	964.00
		20	3/4	1288.00
		25	1	1715.00
		32	1-1/4	2446.00
		40	1-1/2	4905.00
		50	2	8972.00
E-13	 G.M. ELEMS FULLWAY VALVE No. 571 D Standard Pattern Flanged Ends B.S. Table "D" Flanges Hyd. Tested 35 Kg/cm² (500 lbs.)	65	2-1/2	12138.00
		80	3	23117.00
		100	4	45521.00
		125	5	61550.00
		15	1/2	2122.00
		20	3/4	2861.00
		25	1	4461.00
		32	1-1/4	5497.00
E-14	 G.M. ELEMS MAIN COCK POPULAR Screwed Female Ends Light Pattern Hyd. Tested 20 Kg/cm² (300 lbs.)	40	1-1/2	7506.00
		50	2	10650.00
		65	2-1/2	15608.00
		80	3	20583.00
		100	4	35846.00
		125	5	74531.00
		150	6	90759.00
		15	1/2	429.00
E-15	 G.M. ELEMS MAIN COCK No. 506 Screwed Female Ends Standard Pattern Hyd. Tested 20 Kg/cm² (300 lbs.)	20	3/4	632.00
		25	1	869.00
		32	1-1/4	1807.00
		40	1-1/2	2324.00
		50	2	3394.00
		8, 10	1/4, 3/8	451.00
		15	1/2	583.00
		20	3/4	773.00
		25	1	1175.00
		32	1-1/4	2458.00
		40	1-1/2	3185.00
		50	2	4702.00
		65	2-1/2	10424.00
		80	3	16619.00
		100	4	33766.00

	NAME OF ARTICLE	MM	INCH	PRICE RS.
 E-16	G.M. ELEMS	8, 10	1/4, 3/8	658.00
	GLAND COCK No. 508	15	1/2	681.00
		20	3/4	995.00
	Standard Pattern	25	1	1435.00
	Screwed Female Ends	32	1-1/4	3223.00
	Hyd. Tested 20 Kg/cm ²	40	1-1/2	3769.00
	(300 lbs.)	50	2	5860.00
		65	2-1/2	11956.00
 E-17	G.M. ELEMS	15	1/2	1068.00
	GLAND COCK No. 508A	20	3/4	1685.00
	THREE WAY	25	1	2391.00
	Three Way Type	32	1-1/4	4403.00
	"L" and "T" Port Type	40	1-1/2	5932.00
	Screwed Female Ends	50	2	9244.00
	Hyd. Tested 20 Kg/cm ²	65	2-1/2	13644.00
	(300 lbs.)	80	3	20251.00
 E-18	G.M. ELEMS	15	1/2	305.00
	VERTICAL CHECK VALVE	20	3/4	440.00
	POPULAR	25	1	546.00
	Screwed Female Ends	32	1-1/4	1007.00
	Light Pattern	40	1-1/2	1286.00
	female ends	50	2	1911.00
	Hyd. Tested 20 Kg/cm ²	65	2-1/2	3714.00
	(300 lbs.)	80	3	5338.00
 E-19	G.M. ELEMS	15	1/2	462.00
	VERTICAL CHECK VALVE	20	3/4	706.00
	No. 501A	25	1	915.00
	Heavy Pattern	32	1-1/4	1314.00
	Screwed female ends	40	1-1/2	1697.00
	Hyd. Tested 20 Kg/cm ²	50	2	2259.00
	(300 lbs.)	65	2-1/2	3960.00
		80	3	7095.00
 E-20	G.M. ELEMS	15	1/2	305.00
	HORIZONTAL CHECK VALVE	20	3/4	441.00
	POPULAR	25	1	546.00
	Light Pattern	32	1-1/4	1007.00
	Screwed Female Ends	40	1-1/2	1286.00
	Hyd. Tested 10 Kg/cm ²	50	2	1911.00
	(150 lbs.)	65	2-1/2	3714.00
		80	3	5425.00
		100	4	10621.00



INDUSTRIAL VALVES

	NAME OF ARTICLE	MM	INCH	PRICE RS.
 E-21	G.M. ELEMS	4, 8, 10	1/8, 1/4, 3/8	360.00
	HORIZONTAL CHECK	15	1/2	417.00
	VALVE No. 4	20	3/4	654.00
	Medium Pattern	25	1	944.00
	Screwed Female Ends	32	1-1/4	1487.00
	Hyd. Tested 20 Kgf/cm ²	40	1-1/2	1790.00
	(300 lbs.)	50	2	3118.00
		65	2-1/2	5206.00
		80	3	8253.00
		100	4	15131.00
		125	5	28542.00
		150	6	43779.00
 E-22	G.M. ELEMS	8, 10	1/4, 3/8	580.00
	HORIZONTAL CHECK VALVE	15	1/2	631.00
	No. 5	20	3/4	1079.00
	Screwed Female Ends	25	1	1614.00
	Heavy Pattern	32	1-1/4	2274.00
	Hyd. Tested 35 Kgf/cm ²	40	1-1/2	3222.00
	(500 lbs.)	50	2	4900.00
		65	2-1/2	8245.00
		80	3	11801.00
		100	4	19580.00
 E-23	G.M. ELEMS	15	1/2	2066.00
	HORIZONTAL CHECK	20	3/4	2638.00
	VALVE No. 8	25	1	3619.00
	Medium Pattern	32	1-1/4	5018.00
	Flanged Ends	40	1-1/2	5992.00
	B.S. Table "D" Flanges	50	2	8526.00
	Hyd. Tested 20 Kgf/cm ²	65	2-1/2	12013.00
	(300 lbs.)	80	3	16546.00
		100	4	30402.00
		125	5	54505.00
		150	6	69981.00
 E-24	G.M. ELEMS	15	1/2	459.00
	ANGLE CHECK	20	3/4	721.00
	VALVE No. 4	25	1	1036.00
	Medium Pattern	32	1-1/4	1636.00
	Screwed Female Ends	40	1-1/2	1968.00
	Hyd. Tested 20 Kgf/cm ²	50	2	3430.00
	(300 lbs.)			
 E-25	G.M. ELEMS	8, 10	1/4, 3/8	1437.00
	HORIZONTAL CHECK VALVE	15	1/2	1496.00
	No. 9	20	3/4	2215.00
	Screwed Female Ends	25	1	3185.00
	With Renewable stainless Steel Trim	32	1-1/4	4650.00
	Hyd. Tested 40 Kgf/cm ²	40	1-1/2	6388.00
	(600 lbs.)	50	2	9939.00
		65	2-1/2	17671.00
		80	3	26333.00
		100	4	42038.00


	NAME OF ARTICLE	MM	INCH	PRICE RS.
 E-26	G.M. ELEMS	15	1/2	3747.00
	HORIZONTAL CHECK VALVE	20	3/4	4202.00
	No. 9F	25	1	6431.00
	Flanged Ends	32	1-1/4	8704.00
	B.S. Table "F" Flanges	40	1-1/2	10612.00
	with Renewable Stainless	50	2	16481.00
	Steel Trim.	65	2-1/2	32509.00
	Hyd. Tested 40 Kg/cm ² (600 lbs.)	80	3	35126.00
		100	4	52092.00
 E-27	G.M. ELEMS	15	1/2	2300.00
	HORIZONTAL CHECK VALVE	20	3/4	3008.00
	No. 5F	25	1	4044.00
	Heavy Pattern	32	1-1/4	6687.00
	Flanged Ends	40	1-1/2	8348.00
	B.S. Table "F" Flanges	50	2	11457.00
	Hyd. Tested 35 Kg/cm ²	65	2-1/2	18385.00
	(500 lbs.)	80	3	23928.00
		100	4	33246.00
 E-28	G.M. ELEMS	4, 8, 10	1/8, 1/4, 3/8	440.00
	NEEDLE VALVE No. 4	15	1/2	538.00
		20	3/4	779.00
	Medium Pattern	25	1	1101.00
	Screwed Female Ends			
	Hyd. Tested 20 Kg/cm ² (300 lbs.)			
 E-29	G.M. ELEMS	4, 8, 10	1/8, 1/4, 3/8	480.00
	ANGLE NEEDLE	15	1/2	654.00
	VALVE No. 4	20	3/4	915.00
		25	1	1297.00
	Medium Pattern			
	Screwed Female Ends			
	Hyd. Tested 20 Kg/cm ² (300 lbs.)			
 E-30	G.M. ELEMS	8, 10	1/4, 3/8	782.00
	FLUSH COCK No. 515	15	1/2	832.00
		20	3/4	1173.00
	Heavy Pattern	25	1	1809.00
	Screwed Female Ends	32	1-1/4	2366.00
	Hyd. Tested 20 Kg/cm ² (300 lbs.)			


	NAME OF ARTICLE	MM	INCH	PRICE RS.
 E-31	G.M. ELEMS	8, 10	1/4, 3/8	391.00
	FERRULE COCK	15	1/2	488.00
	No. 538 J.C.S.W.R TYPE	20	3/4	762.00
	Rough Body	25	1	1144.00
	Screwed Male Ends	32	1-1/4	2019.00
	Hyd. Tested 20 Kg/cm ²	40	1-1/2	3957.00
	(300 lbs.)	50	2	5455.00
 E-32	BRASS ELEMS	15	1/2	362.00
	STOP COCK NO. 523			
 E-33	BRASS ELEMS	15	1/2	362.00
	BIB COCK			
 E-34	G.M. ELEMS	15	1/2	656.00
	HOSE BIB COCK No. 516	20	3/4	910.00
 E-35	G.M. ELEMS	15	1/2	742.00
	PUSH COCK No. 513	20	3/4	964.00

	NAME OF ARTICLE	MM	INCH	PRICE RS.
 E-36	G.M. ELEMS	15	1/2	188.00
	HOSE COUPLING No. 503	20	3/4	212.00
	Hyd. Tested 20 Kg/cm ² (300 lbs.)	25	1	291.00
 E-37	G.M. ELEMS	8, 10	1/4, 3/8	555.00
	DRAIN COCK No. 535	15	1/2	716.00
	Straight Nose with Round	20	3/4	1126.00
	Metalic Handle	25	1	1793.00
	Hyd. Tested 20 Kg/cm ² (300 lbs.)	32	1 1/4	2282.00
		40	1 1/2	3313.00
		50	2	5628.00
 E-38	G.M. ELEMS	8, 10	1/4, 3/8	438.00
	PET COCK	15	1/2	654.00
	Hyd. Tested 20 Kg/cm ² (300 lbs.)	20	3/4	910.00
		25	1	1684.00
 E-39	G.M. ELEMS	8, 10	1/4, 3/8	440.00
	TAPER COCK No. 519 SCR.	15	1/2	440.00
	Hyd. Tested 20 Kg/cm ² (300 lbs.)	20	3/4	697.00
		25	1	1145.00
 E-40	G.M. ELEMS	8, 10	1/4, 3/8	805.00
	PRESSURE GAUGE COCK	15	1/2	1024.00
	Screwed Female Ends Hyd. Tested 20 Kg/cm ² (300 lbs.)			



	NAME OF ARTICLE	MM	INCH	PRICE RS.
 E-41	G.M. ELEMS	15	1/2	465.00
	UNION COUPLING SCR.	20	3/4	729.00
	Screwed Female Ends	25	1	1273.00
	Hyd. Tested 40 Kg/cm ²	32	1- 1/4	1699.00
	(600 lbs.)	40	1- 1/2	2066.00
		50	2	2646.00
 E-42	G.M. ELEMS	15	1/2	1148.00
	UNION BONNET WHEEL	20	3/4	1810.00
	VALVE No. 9M	25	1	2473.00
	Screwed Female Ends	32	1- 1/4	3801.00
	with Renewable Stainless	40	1- 1/2	5797.00
	Steel Trim	50	2	8901.00
 E-43	G.M. ELEMS	15	1/2	1027.00
	HORIZONTAL CHECK	20	3/4	1591.00
	VALVE No. 9M	25	1	2258.00
	Screwed female ends	32	1- 1/4	3430.00
	with Renewable Stainless	40	1- 1/2	5220.00
	Steel Trim	50	2	7986.00
 E-44	G.M. ELEMS	15	1/2	2266.00
	WHEEL VALVE	20	3/4	2827.00
	L/D & O/S TYPE	25	1	3872.00
	Flanged Ends	32	1- 1/4	5351.00
	B.S. Table "D" Flanges	40	1- 1/2	6564.00
	Medium Pattern	50	2	9161.00
	With Lockable Device &	65	2- 1/2	11770.00
	Open Shut Indicator	80	3	18075.00
	Hyd. Tested 20 Kg/cm ²	100	4	32580.00
	(300 lbs.)	125	5	61636.00
		150	6	80843.00
 E-45	G.M. ELEMS	15	1/2	2277.00
	GATE VALVE	20	3/4	3019.00
	L/D & O/S TYPE	25	1	4677.00
	Flanged Ends	32	1- 1/4	5775.00
	B.S. Table "D" Flanges	40	1- 1/2	7847.00
	Medium Pattern	50	2	11109.00
	With Lockable Device &	65	2- 1/2	16317.00
	Open & Shut Indicator	80	3	21515.00
	Hyd. Tested 20 Kg/cm ²	100	4	39298.00
	(300 lbs.)			

	NAME OF ARTICLE	MM	INCH	PRICE RS.
 E-46	G.M. ELEMS	15	1/2	583.00
	SWING CHECK	20	3/4	993.00
	VALVE	25	1	1356.00
	Screwed Female Ends	32	1- 1/4	1976.00
	Heavy Pattern	40	1- 1/2	2840.00
	Hyd. Tested 20 Kg/cm ²	50	2	3948.00
	(300 lbs.)	65	2- 1/2	7697.00
		80	3	11621.00
		100	4	18835.00
 E-47	G.M. ELEMS	15	1/2	1653.00
	WHEEL VALVE	20	3/4	2143.00
	S.S.F.	25	1	2986.00
	One Side Flange End and other	32	1- 1/4	4315.00
	BSP Screwed Female End	40	1- 1/2	5359.00
	B.S. Table "D" Flange	50	2	7123.00
	Medium Pattern	65	2- 1/2	9425.00
	Hyd. Tested 20 Kg/cm ²	80	3	14204.00
	(300 lbs.)	100	4	26306.00
 E-48	G.M. ELEMS	15	1/2	1765.00
	GATE VALVE	20	3/4	2335.00
	S.S.F.	25	1	3647.00
	One Side Flange End and other	32	1- 1/4	4493.00
	BSP Screwed Female End	40	1- 1/2	6134.00
	B.S. Table "D" Flange	50	2	8703.00
	Standard Pattern	65	2- 1/2	12765.00
	Hyd. Tested 35 Kg/cm ²	80	3	16834.00
	(500 lbs.)	100	4	30365.00
 E-49	G.M. ELEMS	15	1/2	1435.00
	HORIZONTAL CHECK	20	3/4	1826.00
	VALVE S.S.F.	25	1	2588.00
	One Side Flange End and other	32	1- 1/4	3747.00
	BSP Screwed Female End	40	1- 1/2	4623.00
	B.S. Table "D" Flange	50	2	6785.00
	Medium Pattern			
	Hyd. Tested 20 Kg/cm ²			
	(300 lbs.)			
 E-50	G.M. ELEMS	65	2- 1/2	7187.00
	TANKER GATE VALVE	80	3	9860.00
	No. 571-T			
	Screwed Ends			
	Heavy Pattern			
	Split Type Wedge			
	With Sealing Arrangement			
	Hyd. Tested 20 Kg/cm ²			
	(300 lbs.)			


	NAME OF ARTICLE	MM	INCH	PRICE RS.
 E-51	G.M. ELEMS	15	1/2	2390.00
	MAIN COCK	20	3/4	2959.00
	NO. 506 F	25	1	4184.00
	Standard Pattern	32	1- 1/4	7358.00
	Flanged Ends	40	1- 1/2	9294.00
	B.S. Table D Flanges	50	2	12827.00
	Hyd. Tested 20 Kgf/cm ² (300 lbs.)	65	2- 1/2	15447.00
		80	3	22554.00
		100	4	44983.00
 E-52	G.M. ELEMS	15	1/2	2557.00
	GLAND COCK	20	3/4	3188.00
	No. 508 F	25	1	4483.00
	Standard Pattern	32	1- 1/4	8314.00
	Flanged Ends	40	1- 1/2	9901.00
	B.S. Table D Flanges	50	2	13617.00
	Hyd. Tested 20 Kgf/cm ² (300 lbs.)	65	2- 1/2	17010.00
		80	3	24122.00
		100	4	46385.00
 E-53	G.M. ELEMS	15	1/2	3245.00
	WHEEL VALVE	20	3/4	3861.00
	No. 9FM	25	1	5387.00
	Flanged Ends	32	1- 1/4	8256.00
	B.S. Table "F" Flanges with Renewable Stainless Steel Trim	40	1- 1/2	9957.00
	Hyd. Tested 20 Kgf/cm ² (300 lbs.)	50	2	15385.00
 E-54	G.M. ELEMS	15	1/2	3020.00
	HORIZONTAL VALVE	20	3/4	3506.00
	No. 9FM	25	1	5120.00
	Flanged Ends	32	1- 1/4	7497.00
	B.S. Table "F" Flanges with renewable stainless steel Trim.	40	1- 1/2	9677.00
	Hyd. Tested 20 Kgf/cm ² (300 lbs.)	50	2	14301.00
 E-55	G.M. ELEMS	8, 10	1/4, 3/8	393.00
	SPRING SAFETY	15	1/2	915.00
	VALVE No. 520	20	3/4	1282.00
	Open Discharge Type	25	1	1889.00
	Hyd. Tested 20 Kgf/cm ² (300 lbs.)	32	1- 1/4	3091.00
	(Can be set at required pressure)	40	1- 1/2	3811.00
		50	2	5089.00

	NAME OF ARTICLE	MM	INCH	PRICE RS.
 E-56	G.M. ELEMS	15	1/2	1128.00
	SPRING SAFETY VALVE	20	3/4	1561.00
	ENCLOSED BODY	25	1	2266.00
	Angle Pattern Enclosed Body	32	1- 1/4	5250.00
	Hyd. Tested 20 Kg/cm ²	40	1- 1/2	6287.00
	(300 lbs.)	50	2	8569.00
	(Can be set at required pressure)			
 E-57	G.M. ELEMS	15	1/2	2245.00
	PRESSURE REDUCING VALVE	20	3/4	2706.00
	PN-16 COMPACT DESIGN	25	1	3298.00
	Screwed Female Ends	32	1- 1/4	4182.00
	(Option for Pressure Gauge)	40	1- 1/2	6309.00
	Hyd. Tested 20 Kg/cm ²	50	2	7967.00
	(300 lbs.)			
 E-58	G.M. ELEMS	15	1/2	1917.00
	FULLWAY VALVE	20	3/4	2539.00
	No. 571D-M	25	1	3964.00
	Medium Pattern	32	1- 1/4	4884.00
	Flanged Ends	40	1- 1/2	6667.00
	B.S. Table "D" Flanges	50	2	9461.00
	Hyd. Tested 20 Kg/cm ²	65	2- 1/2	13874.00
	(300 lbs.)	80	3	18297.00
		100	4	33006.00
		125	5	58231.00
		150	6	79625.00
 E-59	G.M. ELEMS	15	1/2	1896.00
	SWING CHECK VALVE	20	3/4	2927.00
	Heavy Pattern	25	1	3936.00
	Flanged Ends	32	1- 1/4	6411.00
	B.S. Table "D" Flanges	40	1- 1/2	8040.00
	Hyd. Tested 20 Kg/cm ²	50	2	11918.00
	(300 lbs.)	65	2- 1/2	19213.00
		80	3	24399.00
		100	4	34329.00
 E-60	G.M. ELEMS	15	1/2	921.00
	Y-TYPE STRAINER	20	3/4	1674.00
	Light Pattern	25	1	2691.00
	Screwed Female Ends	32	1- 1/4	4547.00
	Hyd. Tested 20 Kg/cm ²	40	1- 1/2	6510.00
	(300 lbs.)	50	2	12327.00

	NAME OF ARTICLE	MM	INCH	PRICE RS.
 E-61	G.M. ELEMS	15	1/2	1257.00
	GAUGE VALVE	20	3/4	2172.00
	Plug Type Pattern, Single Arm Screwed Male End with Handle operated Hyd. Tested 20 Kg/cm ² (300 lbs.)			
 E-62	S.G. IRON ELEMS	40	1 1/2	732.00
	WAFLER CHECK VALVE	50	2	804.00
		65	2 1/2	962.00
	Nitrite Rubber Liner, in S.G. Iron Body & Flap (Powder Coated), Suitable for insertion between	80	3	1247.00
	Flanges as per ANSIB16.1, Class125, DIN ND10 & BS10 Table-'E'	100	4	1580.00
		125	5	2139.00
		150	6	2754.00
		200	8	3477.00
		250	10	7865.00
		300	12	9789.00
 E-63	S.G. IRON ELEMS	40	1 1/2	1270.00
	BUTTFLY VALVE	50	2	1402.00
		65	2 1/2	1936.00
	Without Lugs, Stainless Steel Stem, EPDM Liner, Suitable for Injection (Powder Coated), Suitable	80	3	2103.00
	for insertion between Flanges as per ANSI-B16.1, Class 125, DIN ND-10 & BS-10 Table-'E'	100	4	2388.00
		125	5	2976.00
		150	6	3659.00
		200	8	4324.00
		250	10	13995.00
		300	12	18212.00
		350	14	29177.00
 E-64	I.C. S.S. BALL VALVE	8	1/4	532.00
	CF-8 (304)	10	3/8	532.00
		15	1/2	532.00
	Full Bore 2 Pc. Design, Blow out Proof Stem, PTFE Seats, Lever Operated, SS	20	3/4	745.00
	(304) Ball & Stem, Screwed Female End. BSP Thread.	25	1"	967.00
	Tested 600 PSIG Hydraulic	40	1 1/2"	1868.00
	100 PSIG Steam	50	2"	3064.00
 E-65	I.C. S.S. BALL VALVE	8	1/4	644.00
	CF-8 (304)	10	3/8	644.00
		15	1/2	644.00
	Full Bore 2 Pc. Design, Blow out Proof Stem, PTFE Seats, Lever Operated, SS	20	3/4	894.00
	(304) Ball & Stem, Screwed Female End. BSP Thread.	25	1"	1287.00
	Tested 1000 PSIG Hydraulic	40	1 1/2"	2528.00
	100 PSIG Steam	50	2"	4131.00
		32	1- 1/4	1908.00

	NAME OF ARTICLE	MM	INCH	PRICE RS.
	I.C. S.S. BALL VALVE	8	1/4	733.00
	CF-8 (304)	10	3/8	733.00
		15	1/2	733.00
	Full Bore 2 Pc. Design, Blow out Proof	20	3/4	1047.00
	Stem, PTFE Seats, Lever Operated, SS	25	1"	1696.00
	(304) Ball & Stem, Screwed Female End.	40	1 1/2"	3377.00
	BSP Thread.	50	2"	5032.00
	Tested 1500 PSIG Hydraulic 180 PSIG Steam			
E-66	with Suitable Teflon upto 250 PSIG (Steam) Rate will be charged extra			
	I.C. CF-8 (S.S. 304) BALL VALVE	25	1"	3410.00
		40	1 1/2"	6035.00
	Three Piece Design, Full Port with S.S. 304	50	2"	8920.00
	Ball & Stem, Renewable Teflon Seat & seals,	65	2 1/2"	13878.00
	Blow out proof stem, S.S. Lever,	80	3	17056.00
	Flanged end to ASA 150#	100	4	27828.00
	ANSI B 16.5 Raised face/Table 'F'			
	Hydr. Body Test : 500 PSIG Hydr. Seat Test : 300 PSIG Pneumatic Seat Test : 100 PSIG			
E-67				
	I.C. CF-8 (S.S. 316) BALL VALVE	25	1"	4022.00
		40	1 1/2"	7118.00
	Three Piece Design, Full Port with S.S. 316	50	2"	9709.00
	Ball & Stem, Renewable Teflon Seat & seals,	65	2 1/2"	14542.00
	Blow out proof stem, S.S. Lever,	80	3	20647.00
	Flanged end to ASA 150#	100	4	34113.00
	ANSI B 16.5 Raised face/Table 'F'			
	Hydr. Body Test : 500 PSIG Hydr. Seat Test : 300 PSIG Pneumatic Seat Test : 100 PSIG			
E-68				
	CAST IRON BALL VALVE	15	1/2"	323.00
		20	3/4"	428.00
	Full Bore 2 Pc. Design,	25	1"	524.00
	SS (304) Ball, Teflon (PTFE) Seats,	32	1 1/4"	1105.00
	Stem Lever Operated, Blow Out Proof Stem,	40	1 1/2"	1301.00
	Screwed Female End.	50	2"	1825.00
	BSP Thread.	65	2 1/2"	3362.00
	Tested 500 PSIG Hydraulic	80	3"	4835.00
	150 PSIG Hydraulic	100	4"	9935.00
E-69				
	CAST IRON BALL VALVE	15	1/2"	914.00
		20	3/4"	1014.00
	Full Bore 3 Pc. Design,	25	1"	1243.00
	SS (304) Ball, Teflon (PTFE) Seats,	32	1 1/4"	1723.00
	Stem Lever Operated, Blow Out Proof Stem,	40	1 1/2"	2142.00
	Flanged Ends to BS-10 Table 'F'.	50	2"	3149.00
	Tested 500 PSIG Hydraulic	65	2 1/2"	5140.00
	150 PSIG Steam	80	3"	6869.00
		100	4"	12084.00
E-70				

NAME OF ARTICLE		MM	INCH	PRICE RS.
	MOULDED SLEEVE SET	15	1/2"	239.00
		20	3/4"	276.00
E-71				
	CAST IRON DUAL PLATE CHECK VALVE	40	1 1/2"	2937.00
		50	2"	3339.00
		65	2 1/2"	3631.00
		80	3	4184.00
		100	4	5270.00
		125	5	6245.00
		150	6	6925.00
		200	8	15163.00
		250	10	22964.00
		300	12	31882.00
		350	14	45690.00
E-72				



	NAME OF ARTICLE	MM	INCH	PRICE RS.
 E-201	G.M. ELEMS	8, 10	1/4, 3/8	772.00
	GATE VALVE IS : 778-1984 CL-1	15	1/2	829.00
	Screwed in Bonnet, Inside Screw	20	3/4	1016.00
	Non Rising Spindle,	25	1	1698.00
	Screwed Female Ends	32	1- 1/4	2373.00
	to IS : 554	40	1- 1/2	3066.00
	Body Hyd. Tested 1.5 Mpa	50	2	4604.00
	Seat Hyd. Tested 1 Mpa	65	2- 1/2	9199.00
		80	3	11965.00
		100	4	22151.00
 E-202	G.M. ELEMS	15	1/2	2651.00
	GATE VALVE IS : 778-1984 CL-1	20	3/4	3175.00
	Screwed in Bonnet, Inside Screw	25	1	4491.00
	Non Rising Spindle,	32	1- 1/4	5800.00
	Flanged Ends	40	1- 1/2	7876.00
	Body Hyd. Tested 1.5 Mpa	50	2	10609.00
	Seat Hyd. Tested 1 Mpa	65	2- 1/2	15473.00
		80	3	21831.00
		100	4	43484.00
 E-203	G.M. ELEMS	15	1/2	674.00
	GLOBE VALVE IS : 778-1984 CL-1	20	3/4	974.00
	Screwed in Bonnet, Inside Screw Rising	25	1	1530.00
	Spindle, Integral Seat,	32	1- 1/4	2151.00
	Screwed Female Ends	40	1- 1/2	2781.00
	to IS : 554	50	2	4315.00
	Body Hyd. Tested 1.5 Mpa	65	2- 1/2	8748.00
	Seat Hyd. Tested 1 Mpa	80	3	11169.00
		100	4	19267.00
 E-204	G.M. ELEMS	15	1/2	2654.00
	GLOBE VALVE IS : 778-1984 CL-1	20	3/4	3186.00
	Screwed in Bonnet, Inside Screw	25	1	3963.00
	Rising Spindle, Flanged Ends	32	1- 1/4	4688.00
	Body Hyd. Tested 1.5 Mpa	40	1- 1/2	7075.00
	Seat Hyd. Tested 1 Mpa	50	2	9114.00
		65	2- 1/2	16955.00
		80	3	19986.00
		100	4	38554.00
 E-205	G.M. ELEMS	15	1/2	638.00
	HORIZONTAL CHECK VALVE	20	3/4	939.00
	IS : 778-1984 CL-1	25	1	1520.00
	Screwed Female Ends	32	1- 1/4	2036.00
	to IS : 554	40	1- 1/2	2753.00
	Body Hyd. Tested 1.5 Mpa	50	2	4176.00
	Seat Hyd. Tested 1 Mpa	65	2- 1/2	8290.00
		80	3	11108.00
		100	4	19292.00

	NAME OF ARTICLE	MM	INCH	PRICE RS.
	G.M. ELEMS	15	1/2	2696.00
	HORIZONTAL CHECK VALVE	20	3/4	3110.00
	IS : 778-1984 CL-1	25	1	3944.00
	Flanged Ends	32	1- 1/4	4639.00
	Body Hyd. Tested 1.5 Mpa	40	1- 1/2	7075.00
	Seat Hyd. Tested 1 Mpa	50	2	9090.00
		65	2- 1/2	16918.00
		80	3	19911.00
		100	4	39060.00
E-206				
	G.M. ELEMS	15	1/2	620.00
	VERTICAL CHECK VALVE	20	3/4	868.00
	IS : 778-1984 CL-1	25	1	1173.00
	Screwed Female Ends	32	1- 1/4	1698.00
	to IS : 554	40	1- 1/2	1970.00
	Body Hyd. Tested 1.5 M Pa	50	2	3149.00
	Seat Hyd. Tested 1 M Pa	65	2- 1/2	4639.00
		80	3	7977.00
		100	4	15256.00
E-207				


**ELQMS®****CERTIFIED BOILER MOUNTINGS**

	NAME OF ARTICLE	MM	INCH	PRICE RS.
E-501	 BRONZE ELEMS GLOBE STEAM STOP VALVE SCR. (St. Screwed) Straight Pattern, Screwed in bonnet, inside screw, rising stem, Renewable stainless Steel (AISI-410) seats and stem with back seat arrangement, Screwed female ends to BSP Taper Handwheel operated. Max. BOP 250 Psig (17.58 Kg/cm ²) at 428° F (220° C) Hyd. Tested 500 Psig (35.15 Kg/cm ²)	15	1/2	2357.00
		20	3/4	2908.00
		25	1	4148.00
		32	1- 1/4	6508.00
		40	1- 1/2	8693.00
		50	2	12330.00
E-502	 BRONZE ELEMS GLOBE STEAM STOP VALVE FLG. (St. Flanged) Straight Pattern, Screwed in bonnet, inside screw, rising stem, Renewable stainless Steel (AISI-410) seats and stem with back seat arrangement, Flanges as per BS : 10 Table "H" Handwheel operated. Max. BOP 250 Psig (17.58 Kg/cm ²) at 428° F (220° C) Hyd. Tested 500 Psig (35.15 Kg/cm ²)	15	1/2	4883.00
		20	3/4	5558.00
		25	1	7051.00
		32	1- 1/4	11690.00
		40	1- 1/2	12582.00
		50	2	17500.00
E-503	 BRONZE ELEMS HORIZONTAL LIFT CHECK VALVE SCR. (St. Screwed) Screwed in Bonnet, Renewable Stainless Steel (AISI-410) Seats, Flanges as per BS : 10 Table "H" Max. BOP 250 Psig (17.58 Kg/cm ²) at 428° F (220° C) Hyd. Tested 500 Psig (35.15 Kg/cm ²)	15	1/2	2262.00
		20	3/4	2784.00
		25	1	3905.00
		32	1- 1/4	5818.00
		40	1- 1/2	8392.00
		50	2	11692.00
E-504	 BRONZE ELEMS HORIZONTAL LIFT CHECK VALVE FLG. (St. Flanged) Screwed in Bonnet, Renewable Stainless Steel (AISI-410) Seats, Flanges as per BS : 10 Table "H" Max. BOP 250 Psig (17.58 Kg/cm ²) at 428° F (220° C) Hyd. Tested 500 Psig (35.15 Kg/cm ²)	15	1/2	4587.00
		20	3/4	5264.00
		25	1	6632.00
		32	1- 1/4	11128.00
		40	1- 1/2	11898.00
		50	2	11653.00
E-505	 BRONZE ELEMS AUXILLARY STEAM STOP VALVE SCR. (St. Screwed) Straight Pattern, outside screw and yoke type, Bolted bonnet, rising stem Renewable Stainless Steel (AISI-410) seats and stem, with back seat arrangement, Screwed female ends to BSP Taper, Hand wheel operated. Max. BOP 250 Psig (17.58 Kg/cm ²) at 428° F (220° C) Hyd. Tested 500 Psig (35.15 Kg/cm ²)	15	1/2	4044.00
		20	3/4	5154.00
		25	1	7841.00
		32	1- 1/4	15266.00
		40	1- 1/2	22651.00
		50	2	27392.00

**ELQMS®****CERTIFIED BOILER MOUNTINGS**

	NAME OF ARTICLE	MM	INCH	PRICE RS.
 E-506	BRONZE ELEMS AUXILLARY STEAM STOP VALVE FLG.	15	1/2	10345.00
		20	3/4	11849.00
		25	1	16041.00
	(St. Flanged) Straight Pattern, outside screw and yoke type, Bolted bonnet, rising stem renewable Stainless Steel (AISI-410) Seats and stem, with back seat arrangement, Flanges per BS: 10	32	1- 1/4	25356.00
	Taper "H" Hand wheel operated	40	1- 1/2	37851.00
	Max. BOP 250 Psig (17.58 Kg/cm ²) at 428° F (220° C)	50	2	49906.00
	Hyd. Tested 500 Psig (35.15 Kg/cm ²)	65	2- 1/2	61092.00
		80	3	81773.00
		100	4	114590.00
 E-507	BRONZE ELEMS HORIZONTAL LIFT CHECK VALVE SCR BOLTED BONNET	40	1- 1/2	17281.00
		50	2	19442.00
	(St. Screwed) Bolted Cover, renewable Stainless Steel (AISI-410) seats. Screwed female ends to BSP Taper	65	2- 1/2	35653.00
	Max. BOP 250 Psig (17.58 Kg/cm ²) at 428° F (220° C) Hyd. Tested 500 Psig (35.15 Kg/cm ²)	80	3	48264.00
 E-508	BRONZE ELEMS HORIZONTAL LIFT CHECK VALVE FLG BOLTED BONNET	40	1- 1/2	22055.00
		50	2	35115.00
	(St. Flanged) Bolted Cover, renewable Stainless Steel (AISI-410) seats. Flanges as per BS : 10 Table "H"			
	Max. BOP 250 Psig (17.58 Kg/cm ²) at 428° F (220° C) Hyd. Tested 500 Psig (35.15 Kg/cm ²)			
 E-509	BRONZE ELEMS FUSIBLE PLUG TWO PIECES DESIGN	15	1/2	1272.00
		20	3/4	1325.00
		25	1	1504.00
	Two Pieces design, Screwed Male	32	1- 1/4	1912.00
	BSP Taper end	40	1- 1/2	2210.00
	Max. BOP 250 Psig (17.58 Kg/cm ²) at 428° F (220° C)	50	2	3249.00
	Hyd. Tested 500 Psig (35.15 Kg/cm ²)			
 E-510	BRONZE ELEMS ACCESSIBLE FEED CHECK VALVE STRAIGHT INLET.	20	3/4	14232.00
		25	1	17562.00
	(Straight Inlet) With double clacks, Angle Pattern, Straight inlet, Bolted bonnet, Stainless Steel (AISI-410) trim and stem Flanges as per BS : 10	32	1- 1/4	21032.00
	Table "H" Handwheel operated.	40	1- 1/2	34470.00
	Max. BOP 250 Psig (17.58 Kg/cm ²) at 428° F (220° C)	50	2	50770.00
	Hyd. Tested 500 Psig (35.15 Kg/cm ²)			

**ELQMS®****CERTIFIED BOILER MOUNTINGS**

	NAME OF ARTICLE	MM	INCH	PRICE RS.
	BRONZE ELEMS	15	1/2	2482.00
	VERTICAL LIFT CHECK	20	3/4	3064.00
	VALVE SCR.	25	1	4278.00
	(Screwed) With renewable Stainless	32	1- 1/4	5256.00
	Steel (AISI-410) Seats, Screwed female	40	1- 1/2	5971.00
	ends to BSP Taper	50	2	7841.00
E-511	Max. BOP 250 Psig (17.58 Kg/cm ²) at 428° F (220° C) Hyd. Tested 500 Psig (35.15 Kg/cm ²)			
	BRONZE ELEMS	15	1/2	5514.00
	VERTICAL LIFT CHECK	20	3/4	6742.00
	VALVE FLG.	25	1	7298.00
	(Flanged) With renewable stainless	32	1- 1/4	9701.00
	steel (AISI-410) Seats, Flanges as per	40	1- 1/2	12212.00
	BS : 10 Table "H"	50	2	18303.00
E-512	Max. BOP 250 Psig (17.58 Kg/cm ²) at 428° F (220° C) Hyd. Tested 500 Psig (35.15 Kg/cm ²)			
	BRONZE ELEMS	15	1/2	4159.00
	CONTROLABLE FEED CHECK	20	3/4	5354.00
	VALVE SCR.	25	1	8076.00
	(Screwed) Straight Pattern, Yoke type	32	1- 1/4	15999.00
	with renewable Stainless Steel (AISI-410)	40	1- 1/2	23752.00
	seats and stem, Screwed female ends	50	2	28747.00
E-513	to BSP Taper, Handwheel operated. Max. BOP 250 Psig (17.58 Kg/cm ²) at 428° F (220° C) Hyd. Tested 500 Psig (35.15 Kg/cm ²)			
	BRONZE ELEMS	15	1/2	11632.00
	CONTROLABLE FEED	20	3/4	14624.00
	CHECK VALVE FLG.	25	1	17645.00
	(Flanged) Straight Pattern, Yoke type	32	1- 1/4	21771.00
	with renewable Stainless Steel (AISI-410)	40	1- 1/2	36779.00
	seats and stem, Flanges as per BS : 10	50	2	52540.00
E-514	Table "H" Handwheel operated. Max. BOP 250 Psig (17.58 Kg/cm ²) at 428° F (220° C) Hyd. Tested 500 Psig (35.15 Kg/cm ²)			
	BRONZE ELEMS	15	1/2	7136.00
	COMBINED COCK AND FEED	20	3/4	8157.00
	CHECK VALVE FLG.	25	1	10129.00
	(Flanged) Flanges as per BS : 10 Table "F"	32	1- 1/4	16299.00
	Max. BOP 150 Psig (10.55 Kg/cm ²) at	40	1- 1/2	20409.00
	428° F (220° C)	50	2	39275.00
E-515	Hyd. Tested 300 Psig (21.10 Kg/cm ²)			

**ELQMS®****CERTIFIED BOILER MOUNTINGS**

	NAME OF ARTICLE	MM	INCH	PRICE RS.
	BRONZE ELEMS	15	1/2	1319.00
	"Y" TYPE STRAINER SCR.	20	3/4	2904.00
		25	1	5516.00
	(Screwed) With Brass/SS sheet screen, Screwed female ends to BSP Taper	32	1- 1/4	8043.00
	Max. BOP 250 Psig (17.58 Kg/cm ²) at 428° F (220° C)	40	1- 1/2	9786.00
	Hyd. Tested 500 Psig (35.15 Kg/cm ²)	50	2	13282.00
E-516				
	BRONZE ELEMS	15	1/2	2739.00
	"Y" TYPE STRAINER FLG.	20	3/4	6645.00
		25	1	10427.00
	(Flanged) With Brass/SS Sheet Screen, Flanges as per BS. : 10 Table "H"	32	1- 1/4	16036.00
	Max. BOP 250 Psig (17.58 Kg/cm ²) at 428° F (220° C)	40	1- 1/2	18551.00
	Hyd. Tested 500 Psig (35.15 Kg/cm ²)	50	2	29081.00
E-517				
	BRONZE ELEMS SPRING	15	1/2	7959.00
	LOADED SAFETY VALVE	20	3/4	10168.00
	OPEN DISCHARGE SCR.	25	1	10787.00
	(St. Screwed) Pop Type, Open discharge straight Pattern	32	1- 1/4	16572.00
	Screwed Male inlet to 428° F (220° C)	40	1- 1/2	25126.00
	Max. BOP 250 Psig (17.58 Kg/cm ²) at 428° F (220° C)	50	2	38389.00
E-518				
	BRONZE ELEMS	15	1/2	7959.00
	SPRING LOADED SAFETY VALVE	20	3/4	10168.00
	ENCLOSED DISCHARGE SCR.	25	1	10787.00
	(Angle Screwed) Pop Type, Enclosed discharge Angle Pattern	32	1- 1/4	16572.00
	Screwed Male inlet & Female outlet to BSP Taper.	40	1- 1/2	25126.00
	Max. BOP 250 Psig (17.58 Kg/cm ²) at 428° F (220° C)	50	2	38389.00
E-519				
	BRONZE ELEMS	15	1/2	9725.00
	SPRING LOADED SAFETY VALVE	20	3/4	12127.00
	OPEN DISCHARGE FLG.	25	1	14574.00
	(St. Flanged) Pop Type, Open discharge, Stainless Steel	32	1- 1/4	22016.00
	Flanges as per BS : 10 Table "H"	40	1- 1/2	29537.00
	Max. BOP 250 Psig (17.58 Kg/cm ²) at 428° F (220° C)	50	2	42893.00
E-520				

**ELQMS®****CERTIFIED BOILER MOUNTINGS**


	NAME OF ARTICLE	MM	INCH	PRICE RS.
E-521	 BRONZE ELEMS SPRING LOADED SAFETY VALVE ENCLOSED DISCHARGE FLG. (Angle Flanged) Pop Type, Enclosed Discharge, Angle Pattern Flanges as per BS : 10 Table "H" Max. BOP 250 Psig (17.58 Kg/cm ²) at 428° F (220° C) Hyd. Tested 500 Psig (35.15 Kg/cm ²)	15	1/2	9007.00
		20	3/4	12127.00
		25	1	14574.00
		32	1- 1/4	22016.00
		40	1- 1/2	29537.00
		50	2	42893.00
E-522	 BRONZE ELEMS DIAPHRAM TYPE PRESSURE REDUCING VALVE SCR. With Metallic diaphragm, screwed female ends to BSP Taper, Max. BOP 250 Psig (17.58 Kg/cm ²) at 428° F (220° C) Hyd. Tested 500 Psig (35.15 Kg/cm ²) Pressure Range 5/60, 20/80, 40/125.	15	1/2	9590.00
		20	3/4	13904.00
		25	1	18480.00
		32	1- 1/4	26077.00
		40	1- 1/2	29365.00
		50	2	42665.00
E-523	 BRONZE ELEMS PARALLEL SLIDE VALVE FLG. Heavy Pattern, Rack and pinion operated, Stainless Steel (AISI-410)/Monel seats, with operating key. Flanges as per Table "H" Max. BOP 250 Psig (17.58 Kg/cm ²) at 428° F (220° C)	25	1	22653.00
		32	1- 1/4	27054.00
		40	1- 1/2	30918.00
		50	2	48464.00
E-524	 BRONZE ELEMS SLEEVE PACKED WATER LEVEL GAUGE VALVE SCR. Screwed Male ends Automatic shut off device in water arm. Max. BOP 250 Psig (17.58 Kg/cm ²) at 428° F (220° C) Hyd. Tested 500 Psig (35.15 Kg/cm ²) NOTE : Spare moulded Asbestos sleeves, if required can be supplied at an extra cost. Please also state if left hand or right hand set is required.	15	1/2	16633.00
		16	5/8	17778.00
		20	3/4	17778.00
E-525	 BRONZE ELEMS SLEEVE PACKED WATER LEVEL GAUGE VALVE FLG. Flanges as per BS : 10 Table "H" Automatic shut off device in water arm Max. BOP 250 Psig (17.58 Kg/cm ²) at 428° F (220° C) Hyd. Tested 500 Psig (35.15 Kg/cm ²) NOTE : Spare moulded Asbestos sleeves, if required can be supplied at an extra cost. Please also state if left hand or right hand set is required.	15	1/2	17202.00
		16	5/8	18350.00
		20	3/4	18350.00

**ELQMS®****CERTIFIED BOILER MOUNTINGS**

	NAME OF ARTICLE	MM	INCH	PRICE RS.
	BRONZE ELEMS	15	1/2	9656.00
	ASBESTOS PACKED WATER	16	5/8	12267.00
	LEVEL GAUGE VALVE FLG.	20	3/4	12267.00
	(Flanged) Flanges as per B.S. Table "F" Max. BOP 150 Psig (10.55 Kg/cm ²) at 428° F (220° C) Hyd. Tested 300 Psig (21.1 Kg/cm ²) Please also state if left hand or right hand set is required.			
E-526				
	BRONZE ELEMS	15	1/2	9830.00
	ASBESTOS PACKED WATER	16	5/8	12509.00
	LEVEL GAUGE VALVE SCR.	20	3/4	12509.00
	(Screwed) Male ends Max. BOP 150 Psig (10.55 Kg/cm ²) at 428° F (220° C) Hyd. Tested 300 Psig (21.1 Kg/cm ²) Please also state if left hand or right hand set is required.			
E-527				
	BRONZE ELEMS	15	1/2	795.00
	FUSIBLE PLUG ONE PIECE	20	3/4	823.00
	DESIGN	25	1	1338.00
	One pc. design, Screwed male end to BSP Taper end. Max. BOP 100 Psig upto 250 psig (17.58 Kg/cm ²) at 428° F (220° C) Hyd. Tested 500 Psig (35.15 Kg/cm ²)			
E-528				
	BRONZE ELEMS	15	1/2	2503.00
	THERMODYNAMIC STEAM	20	3/4	3433.00
	TRAP	25	1	6123.00
	With integral SS (AISI-304) strainer Screwed male end to BSP Taper Max. BOP 250 Psig (17.58 Kg/cm ²) at 428° F (220° C) Hyd. Tested 500 Psig (35.15 Kg/cm ²)			
E-529				
	BRONZE ELEMS	15	1/2	2429.00
	RELIEF VALVE	20	3/4	3367.00
	SPRING LOADED TYPE	25	1	4530.00
	Enclosed Discharge (Angle Type) Screwed Male BSP Inlet & female BSP outlet, Max. Set Pressure 150 Psig (10.55 Kg/cm ²) at Max. Temp. 428° F (220° C)	32	1- 1/4	7537.00
		40	1- 1/2	8450.00
		50	2	12336.00
E-530				

	NAME OF ARTICLE	MM	INCH	PRICE RS.
	BRONZE ELEMS	15	1/2	2146.00
	SIGHT GLASS	20	3/4	2170.00
		25	1	2434.00
	With Barosil Toughened Glass	32	1- 1/4	3632.00
	Screwed Female Ends to	40	1- 1/2	5016.00
	BSPT Threads	50	2	6256.00
	Max. BOP 250 Psig at 428° F (220° C)			
E-531				
	BRONZE ELEMS	15	1/2	3656.00
	GAUGE GLASS COCK PROTECTOR ASSEMBLY	20	3/4	4142.00
	Protector Shoe			
	NOTE : The cost of toughened glass will be charged extra as actual as per size required			
E-532				


**ELQMS®****CERTIFIED BOILER MOUNTINGS**

	NAME OF ARTICLE	MM	INCH	PRICE RS.
E-1001	 CAST IRON ELEMS GLOBE STEAM STOP VALVE PN-16 (St. Pattern) Bolted Bonnet, Outside Screw & Yoke Type, Rising Stem with Back Seat Arrangement, Renewable Stainless Steel (AISI-410) Trim Hand Wheel Operated. Flanges as per BS : 5152 (PN 16) Hyd. Tested to 370 psig (26 Kg/cm ²) Seat tested to 230 Psig (16 Kg/cm ²)	15	1/2	1800.00
		20	3/4	1891.00
		25	1	2119.00
		32	1- 1/4	3146.00
		40	1- 1/2	3854.00
		50	2	4918.00
		65	2- 1/2	6980.00
		80	3	9589.00
		100	4	13676.00
		125	5	17466.00
E-1002	 CAST IRON ELEMS HORIZONTAL LIFT CHECK VALVE PN-16 (St. Pattern) Bolted bonnet, Renewable Stainless Steel (AISI-410) Trim. Flanges as per BS : 5152 (PN 16) Hyd. Tested to 370 psig (26 Kg/cm ²) Scot tested to 230 Psig (16 Kg/cm ²)	15	1/2	1774.00
		20	3/4	1839.00
		25	1	2094.00
		32	1- 1/4	2748.00
		40	1- 1/2	3491.00
		50	2	4182.00
		65	2- 1/2	6144.00
		80	3	8478.00
		100	4	11700.00
		125	5	15725.00
E-1003	 CAST IRON ELEMS "Y" TYPE STRAINER Y-Type strainer, with stainless steel (AISI 304) Perforated Sheet Screen, screwed female ends to BSP thread. Hyd. Tested to 300 psig (20 Kg/cm ²)	15	1/2	367.00
		20	3/4	563.00
		25	1	839.00
		32	1- 1/4	1151.00
		40	1- 1/2	1471.00
		50	2	2482.00
E-1004	 CAST IRON ELEMS "Y" TYPE STRAINER Y-Type strainer, with Stainless Steel (AISI 304) Perforated Sheet Screen, Flanges as Per BS : 10 Table. "F" Hyd. tested to 300 Psig (20 Kg/cm ²)	15	1/2	1151.00
		20	3/4	1373.00
		25	1	2162.00
		32	1- 1/4	3317.00
		40	1- 1/2	3491.00
		50	2	5207.00
		65	2- 1/2	8086.00
		80	3	9018.00
		100	4	15439.00
		125	5	21285.00
E-1005	 CAST IRON ELEMS JUNCTION STEAM STOP VALVE Right angle Pattern, bolted bonnet, outside screw & Yoke type rising stem with back seat arrangement renewable stainless steel (AISI 304) Trim, hand wheel Operated Flanges as per BS : 10 5152 (PN 16) Hyd. tested to 370 lbs. (26 Kg/cm ²) seat tested 230 lbs. (16 Kg/cm ²)	15	1/2	1766.00
		20	3/4	1857.00
		25	1	2080.00
		32	1- 1/4	3089.00
		40	1- 1/2	3764.00
		50	2	4807.00
		65	2- 1/2	6846.00
		80	3	9428.00
		100	4	13245.00

**ELQMS®****CERTIFIED BOILER MOUNTINGS**

	NAME OF ARTICLE	MM	INCH	PRICE RS.
	CAST IRON ELEMS	15	1/2	1566.00
	LIFT CHECK (NON RETURN)	20	3/4	1805.00
	VALVE RIGHT ANGLE	25	1	1931.00
	Right angle Pattern, Bolted Bonnet, Renewable	32	1- 1/4	2698.00
	Stainless Steel (AISI-410) Trim	40	1- 1/2	3079.00
	Flanges as per BS : 5152 (PN-16)	50	2	4102.00
	Hyd. tested to 370 lbs. (26 Kg/cm ²)	65	2- 1/2	6034.00
	Seat tested 230 lbs. (16 Kg/cm ²)	80	3	8318.00
E-1006		100	4	11301.00
	CAST IRON ELEMS	15	1/2	2319.00
	VERTICAL INVERTED	20	3/4	3014.00
	BUCKET TYPE STEAM TRAP	25	1	4551.00
	Screwed Female Ends	32	1- 1/4	7997.00
	Suitable for Saturated Steam	40	1- 1/2	10782.00
	With AISI 304 working Parts	50	2	13566.00
E-1007	Max BOP 150 Psig (10.55 Kg/cm ²) at 428° F (220° C)			
	CAST IRON ELEMS	25	1	11818.00
	ACCESSIBLE FEED	40	1- 1/2	17103.00
	CHECK VALVE	50	2	24047.00
	(Straight Inlet) Angle	65	2- 1/2	29095.00
	Pattern, Bolted Bonnet, with SS-410 trim,			
E-1008	Flanges As per BS : 10 Table-F, Max BOP 150 Psig (10.55 Kg/cm ²) at 428° F (220° C)			
	CAST IRON ELEMS	25	1	8219.00
	MOISTURE SEPERATOR	40	1- 1/2	9033.00
	Flanges As per BS : 10 Table-F,	50	2	13841.00
	Max BOP 150 Psig (10.55 Kg/cm ²) at 428° F (220° C)	65	2- 1/2	20155.00
		80	3	23652.00
		100	4	45842.00
E-1009				


**ELQMS®****CERTIFIED BOILER MOUNTINGS**

	NAME OF ARTICLE	MM	INCH	PRICE RS.
E-2001	 CAST STEEL ELEMS GLOBE STEAM STOP VALVE PN-40 Bolted Bonnet, Outside Screw & Yoke Type, Rising Stem with Back Seat Arrangement, Renewable Stainless Steel (AISI-410) Trim. Hand wheel operated Flanges As per BS : 4504 (PN-40) Hyd. Tested 852 Psig (60 Kg/cm ²) Seat Tested to 568 Psig (40 Kg/cm ²)	15	1/2	3629.00
		20	3/4	3985.00
		25	1	4672.00
		32	1- 1/4	6361.00
		40	1- 1/2	7082.00
		50	2	9074.00
		65	2- 1/2	13646.00
		80	3	17330.00
		100	4	22497.00
		125	5	31568.00
		150	6	49215.00
		200	8	91974.00
E-2002	 CAST STEEL ELEMS HORIZONTAL CHECK VALVE PN-40 Bolted bonnet renewable stainless Steel (AISI-410) Trim. Flanges As per BS : 4504 (PN-40) Hyd. Tested 852 Psig (60 Kg/cm ²) Seat Tested to 568 Psig (40 Kg/cm ²)	15	1/2	3265.00
		20	3/4	3533.00
		25	1	4125.00
		32	1- 1/4	5722.00
		40	1- 1/2	6375.00
		50	2	8160.00
		65	2- 1/2	12282.00
		80	3	15594.00
		100	4	20242.00
		125	5	28410.00
		150	6	44293.00
		200	8	82770.00
E-2003	 CAST STEEL ELEMS BLOW OFF VALVE Flanges ends as per per BS : 10 Table J Bolted bonnet, renewable Stainless Steel (AISI-410) seats & trim, rack & pinion operated, with operating key Hyd. Test Pressure Body (91.42 Kg/cm ²) Seat (45.71 Kg/cm ²) NOTE : Flanges as per Class 300 are also available with an increase of 10% of prices mentioned	25	1	12547.00
		40	1- 1/2	16030.00
		50	2	21401.00
E-2004	 CAST STEEL ELEMS SLEEVE PACKED WATER LEVEL GAUGE VALVE FLG. Flanges as per BS : 10 Table "J" Automatic shut off device in water arm Max. BOP 350 Psig (24.60 Kg/cm ²) at 750° F (400° C) Hyd. Tested 700 Psig (49.22 Kg/cm ²) NOTE : Please also state if left hand or right hand set is required.	15	1/2	12839.00
		16	5/8	13612.00
		20	3/4	13612.00
E-2005	 S. S. ELEMS THERMODYNAMIC STEAM TRAP WITH STRAINER (With Strainer) Stainless Steel (AISI-410) Working parts, with SS. (AISI-304) Strainer. Screwed female ends to BSP Taper Max BOP 450 PSIG (31.5 Kg/cm ²) at 750° F Hyd. Tested 900 Psig (63 Kg/cm ²)	15	1/2	2154.00
		20	3/4	2968.00
		25	1	3864.00

**ELQMS®****CERTIFIED BOILER MOUNTINGS**

	NAME OF ARTICLE	MM	INCH	PRICE RS.
 E-2006	I.C. ELEMS	15	1/2	1794.00
	STAINLESS STEEL	20	3/4	1974.00
	THERMODYNAMIC STEAM TRAP	25	1	2094.00
	Screwed Female BSP Threads, with S.S. Trim & with S.S. (304) Strainer Test Pressure 600 PSIG Hyd.			
 E-2007	CAST STEEL ELEMS	25x40	1x1 - 1/2	30133.00
	SPRING LOADED FULL	25x50	1x2	33074.00
	LIFT SAFETY VALVE	40x50	1 - 1/2x2	37403.00
	With SS Working parts, Max Set Pressure 250 PSIG Steam Body Test Pressure 500 PSIG Hyd. Inlet Flanges as per NS 10 Table-H Outlet Flanges as per BS 10 Table-J	50x80	2x3	67822.00
		80x100	3x4	76156.00
		100x150	4x6	113681.00
 E-2008	CAST STEEL ELEMS	25	1	5705.00
	Y-TYPE STRAINER	40	1 - 1/2	8041.00
	Y-Type Strainer, Flanges Ends as per Bs10 Table-J with SS screen, Max Working Pressure 350 PSIG Steam Body Test Pressure 700 PSIG Hyd.	50	2	9640.00
		65	2 - 1/2	11697.00
		80	3	21808.00
		100	4	30749.00
		150	6	74525.00
		200	8	103584.00
 E-2009	I.C. ELEMS	15	0.50	726.00
	WAFER TYPE SLAM	20	3/4	863.00
	CHECK VALVE (CF8M)	25	1	1093.00
	With SS Spring, suitable for Bs10 Table E, F, H, PN-40, CI-150, CI- Body Test Pressure 700 PSIG Hyd.	32	1 - 1/4	1674.00
		40	1 - 1/2	1821.00
		50	2	2887.00
		65	2 - 1/2	4677.00
		80	3	5127.00
		100	4	5127.00
		125	5	7726.00
		150	6	
		200	8	
		250	10	
		300	12	
 E-2010	CAST STEEL ELEMS	25	1	27126.00
	ACCESSIBLE FEED	40	1 - 1/2	35231.00
	CHECK VALVE	50	2	46270.00
	Straight Inlet, Angle Pattern, Bolted Bonnet with SS-410 Trim, Flanges as per Table-J, Max. BOP 250 PSIG at 220° C			

	NAME OF ARTICLE	CTC	MM	INCH	PRICE RS.
E-2011	CAST STEEL ELEMS	400MM	20	3/4	21332.00
	REFLEX / TRANSPARENT	450MM	20	3/4	23459.00
	FLAT GLASS LEVEL	500MM	20	3/4	25812.00
	GAUGE FLG. CL-300				
	Flanged Ends ASTM A216 Gr.WCB, Integral offset needle type Isolating valves & Drain valve, Tempered Borosilicate Glass, capsule type auto ball check facility. Hyd. Test pressure - 70 Kg/cm ² Working pressure - 35 Kg/cm ² Design temperature - 425°C				
E-2012	CAST STEEL ELEMS		15	1/2	1837.00
	GLOBE STEAM STOP		20	3/4	2230.00
	VALVE (PN40)		25	1	3132.000
	Stainless Steel (CF8), Screwed in bonnet, Rising stem, Handwheel Operated, Screwed female ends to BSP/BSPT/NPT or Socket Weld type. Hyd. Test pressure (Body 60 Bar), (Seat 44 Bar) Design temperature - 425°C				

	NAME OF ARTICLE	MM	INCH	PRICE RS.
 E-5001	BRASS ELEMS	8, 10	1/4, 3/8	294.00
	BALL VALVE PN-32	15	1/2	346.00
		20	3/4	481.00
	Screwed Female End	25	1	754.00
	With Chrome Plated Brass working Parts	32	1- 1/4	1365.00
	Two Peice Design	40	1- 1/2	1761.00
	Hyd. Tested 20 Kg/cm ²	50	2	2647.00
	(300 lbs.)	65	2 1/2	6117.00
		80	3	8581.00
		100	4	14709.00
 E-5002	FORGED BRASS ELEMS	15	1/2	422.00
	AIR VENT VALVE			
	Screwed Male Inlet			
 E-5003	FORGED BRASS ELEMS	15	1/2	224.00
	Y-TYPE STRAINER	20	3/4	359.00
		25	1	430.00
	Screwed Female Ends,	40	1-1/2	1382.00
	with brass screen	50	2	1571.00
		32	1-1/4	2676.00
 E-5004	BRASS ELEMS	15	1/2	253.00
	SWING CHECK VALVE PN-25	20	3/4	391.00
		25	1	633.00
	Screwed Female End	32	1- 1/4	1094.00
	with Brass working Parts	40	1- 1/2	1515.00
	Hyd. Tested 20 kgfcm	50	2	2323.00
	(300 lbs.)			
 E-5005	CAST STEEL ELEMS	25	1	4272.00
	GATE VALVE CLASS-150	32	1-1/4	6418.00
		40	1-1/2	7397.00
	Bolted bonnet, O.S. & Y. Type, Rising stem &	50	2	9860.00
	Non Rising Handwheel operated,	65	2-1/2	12655.00
	with renewable Stainless	80	3	15778.00
	Steel Trim, Mfg. as per ANSI 16.5 R/F CI-150	100	4	22514.00
	Testing Standard API 598	125	5	31999.00
	Body Test Pressure : 30 Bar Gauge Hyd.	150	6	35663.00
	Seat Test Pressure : 22 Bar Gauge Hyd.	200	8	75504.00
	: 6.9 Bar Gauge (Air)	250	10	117509.00
		300	12	164204.00

	NAME OF ARTICLE	MM	INCH	PRICE RS.
 E-5006	CAST STEEL ELEMS	25	1	5081.00
	GLOBE VALVE CLASS-150	32	1- 1/4	6850.00
		40	1- 1/2	7397.00
	Bolted bonnet, O.S. & Y. Type, Rising stem & Handwheel operated, with renewable Stainless	50	2	10516.00
	Steel Trim, Mfg. as per ANSI 16.5 R/F CI-150	65	2- 1/2	14462.00
	Testing Standard API 598	80	3	18078.00
	Body Test Pressure : 30 Bar Gauge Hyd.	100	4	28430.00
	Seat Test Pressure : 22 Bar Gauge Hyd.	125	5	41571.00
	: 6.9 Bar Gauge (Air)	150	6	47152.00
		200	8	76915.00
		250	10	121960.00
		300	12	170263.00
 E-5007	CAST STEEL ELEMS	25	1	4025.00
	SWING CHECK VALVE	40	1- 1/2	6738.00
	CLASS-150	50	2	8052.00
	Bolted cover, with renewable Stainless	65	2- 1/2	10191.00
	Steel Trim, Mfg. as per API 600 /BS/1414 /ASME	80	3	12491.00
	B 16.34, Flanges as per ANSI 16.5 R/F CI-150	100	4	19065.00
	Testing Standard API 598	125	5	29286.00
	Body Test Pressure : 30 Bar Gauge Hyd.	150	6	34183.00
	Seat Test Pressure : 22 Bar Gauge Hyd.	200	8	56206.00
		250	10	106301.00
		300	12	154003.00
 E-5008	CAST STEEL ELEMS	25	1	6415.00
	GATE VALVE	32	1- 1/4	8827.00
	CLASS-300	40	1- 1/2	9636.00
	Bolted bonnet, O.S. & Y. Type, Rising stem & Non Rising Handwheel operated, with renewable Stainless	50	2	14781.00
	Steel Trim, Mfg. as per API 600 /BS/1414 /ASME	65	2- 1/2	20326.00
	B 16.34, Flanges as per ANSI 16.5 R/F CI-300	80	3	26443.00
	Testing Standard API 598	100	4	35979.00
	Body Test Pressure : 76 Bar Gauge Hyd.	125	5	47712.00
	Seat Test Pressure : 55 Bar Gauge Hyd.	150	6	69239.00
	: 6.9 Bar Gauge (Air)	200	8	133770.00
		250	10	203315.00
		300	12	251424.00
 E-5009	CAST STEEL ELEMS	25	1	7629.00
	GLOBE VALVE	32	1- 1/4	9861.00
	CLASS-300	40	1- 1/2	10303.00
	Bolted bonnet, O.S. & Y. Type, Rising stem & Handwheel operated, with renewable Stainless	50	2	19314.00
	Steel Trim, Mfg. as per API 600 /BS/1414 /ASME	65	2- 1/2	24683.00
	B 16.34, Flanges as per ANSI 16.5 R/F CI-300	80	3	31731.00
	Testing Standard API 598	100	4	47011.00
	Body Test Pressure : 76 Bar Gauge Hyd.	125	5	61925.00
	Seat Test Pressure : 55 Bar Gauge Hyd.	150	6	71685.00
	: 6.9 Bar Gauge (Air)	200	8	96732.00
		250	10	177149.00
		300	12	243134.00
 E-5010	CAST STEEL ELEMS	40	1- 1/2	4503.00
	SWING CHECK VALVE	50	2	7198.00
	CLASS-300	65	2- 1/2	9692.00
	Bolted cover, with renewable Stainless	80	3	11895.00
	Steel Trim, Mfg. as per API 600 /BS/1414 /ASME	100	4	16653.00
	B 16.34, Flanges as per ANSI 16.5 R/F CI-300	125	5	20708.00
	Testing Standard API 598	150	6	31010.00
	Body Test Pressure : 76 Bar Gauge Hyd.	200	8	43667.00
	Seat Test Pressure : 55 Bar Gauge Hyd.	250	10	66539.00
		300	12	121605.00
				217770.00

		NAME OF ARTICLE	MM	INCH	PRICE RS.
 E-6001	FORGED STEEL (A 105) ELEMS	15	1/2	1695.00	
	GATE VALVE SCREWED/S/W	20	3/4	1960.00	
	FEMALE ENDS	25	1	2957.00	
	Standard Bore, Bolted Bonnet, O.S. & Y Type, Rising Stem with back seat arrangement, conforming to BS : 5352/API 602 Class-800 Body Tested to 3000 Psig Hyd. Seat tested to 2200 Psig & 100 Psig Air	32	1- 1/4	4464.00	
		40	1- 1/2	6621.00	
		50	2	8185.00	
 E-6002	FORGED STEEL (A 105) ELEMS	15	1/2	1732.00	
	GLOBE VALVE SCREWED/S/W	20	3/4	1960.00	
	FEMALE ENDS CL-800	25	1	2932.00	
	Standard Bore, Bolted Bonnet, O.S. & Y Type, Rising Stem with back seat arrangement, conforming to BS : 5352/API 602 Class-800 Body Tested to 3000 Psig Hyd. Seat tested to 2200 Psig & 100 Psig Air	32	1- 1/4	4401.00	
		40	1- 1/2	6002.00	
		50	2	8142.00	
 E-6003	FORGED STEEL (A 105) ELEMS	15	1/2	1382.00	
	HORIZONTAL LIFT CHECK VALVE	20	3/4	1467.00	
	SCREWED/S/W FEMALE ENDS	25	1	2037.00	
	CL-800	32	1- 1/4	3645.00	
	Standard Bore, bolted bonnet, conforming to BS : 5352/API 602 Class-800 Body Tested to 3000 Psig Hyd. Seat tested to 2200 Psig & 100 Psig Air	40	1- 1/2	5028.00	
		50	2	7637.00	

Terms & Conditions of Sale

1. All orders placed direct or through our representatives are subject to confirmation by the Head Office.
2. All Goods are booked at carriers risk and we do not accept any responsibility for loss, damage or pilferage in transit. If desired, we can get the goods insured at customer's cost.
2. Our Prices are F.O.R. Jalandhar.
4. Every consignment despatched from here contains Packing Note. Any shortage found in package received intact should be reported to us within 7 days from the date of delivery for verification, otherwise no claim will be entertained.
5. Order once placed and confirmed by us cannot be cancelled without our consent. We reserve the right to execute any order in full or by part according to our supply position. We accept no responsibility for delayed supply for reasons beyond our control.
6. Railway Receipt or G.R. for the goods supplied, shall be negotiated through scheduled Bank against payment only.
7. Central Sales Tax, Punjab Sales Tax and Central Excise Duty will be charged extra as applicable at the time of despatch.
8. New customer's are required to remit 25% of the value of the order in advance.
9. If any legal issue is involved it will be subject to the Jurisdiction of Jalandhar Courts only.

Notes

1. For other sizes and types of valves, cocks & boiler mountings not covered in this list, rate will be furnished on request.
2. Test certificate in Form III-C as per IBR duly signed by the Director of Boilers, Punjab will be supplied along with each valve covered under Indian Boiler Regulations.

PUNJAB METAL WORKS

AN ISO 9001:2015 CO.

G.T. Road, Maqsudan, Jalandhar-144008

Tel. : 0181-2672366, 5054488

E-mail : sales@elemsvalves.com | info@elemsvalves.com | marketing@elemsvalves.com

Website : www.elemsvalves.com